

户外 单相 环氧树脂浇注式  
OUTDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data



- 产品性能符合标准 GB1208和IEC60044-1  
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 40.5/95/185kV  
Rated insulation level 40.5/95/185kV
- 额定二次电流: 5A或1A  
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz  
Rated frequency 50Hz or 60Hz
- 环境温度: -25℃~+40℃  
Ambient temperature -25℃~+40℃

额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)				一秒短时热电流 1s short-time thermal current(kA)	动稳定电流 Rated dynamic current (kA)
		0.2S	0.2	0.5	10P10		
30-100	0.2/0.2 0.2/0.5	15	30	30	50	150 lth/2	375 lth
150						31.5/1	80
200	0.5/0.5					31.5/2	80
300-500	0.2/10P10					31.5/3	80
600-800	0.5/10P10					31.5/4	80
1000-2000	0.2S/0.5/10P10					30	40

外形及安装尺寸 Overall dimension drawing

